

B203

JP03091722

**DRIVING METHOD FOR ELECTROPHORESIS DISPLAY ELEMENT**

TOYOTA MOTOR CORP

**Inventor(s): ; NAKAMURA NAOKI ; TOSHIMA KAZUO****Application No. 01228697, Filed 19890904, Published 19910417**

**Abstract:** PURPOSE: To obtain the coloring state of a display element by applying 1st DC high voltage to a translucent type electrophoresis display element and then applying and holding a 2nd DC low voltage to obtain the translucent state of the display element and applying an AC voltage to a transparent electrode film.

CONSTITUTION: The 1st DC high voltage  $V_1$  of 300V is applied between the transparent electrodes 2a and 2b so that the polarity of the mesh or striped transparent electrode film 2b is opposite from the polarity of the electrostatic charging of dispersed particles 3. Then the 2nd DC low voltage  $V_2$  of 100V is applied between the transparent electrodes 2a and 2b and held so that the polarity of the mesh or striped transparent electrode film 2b is opposite from the polarity of the electrostatic charging of the dispersed particles 3, thereby obtaining the translucent state of the display element. Then the sine wave of 50Hz in frequency and 150V in voltage  $V_3$  is applied between the transparent electrodes 2a and 2b as an AC voltage to obtain the coloring state.

COPYRIGHT: (C)1991; JPO&amp;Japio

Int'l Class: G02F00119; G09G00316

MicroPatent Reference Number: 000142580

COPYRIGHT: (C)JPO